



4T430CSS0x1 - 4T430CSE0x1 - 4T430CSX0x1

30,000 lbs. Capacity

- Flat Deck models -
Choice of three different lengths
- 24" wide adjustable runways
- Solid 13" Pulleys and 5/8" DIA Steel cables
- Air Operated Stainless Steel Air release cylinders
- Powerpack operator controls can be located on front driver side or rear passenger side
- No vehicle door damage with hidden cylinder under the runway
- Adjustable safety lock ladders level the runways and compensate for uneven floors
- Add optional rolling air/hydraulic jacks for the ultimate in complete vehicle servicing
- 230V - 1 phase - 60 Hz - 20 Amp power required
(optional 230V - 3 phase powerpack available)



Available Accessories

Rolling Air Hydraulic Jacks 4TRJ15000



SPECIFICATIONS

4T430CSS0x1 - 4T430CSE0x1 - 4T430CSX0x1

Capacity	30,000 lbs	8636 kg
Overall Length 4T430CSS0x1	328 1/4"	8338 mm
Overall Length 4T430CSE0x1	364 1/4"	9252 mm
Overall Length 4T430CSX0x1	400 1/4"	10166 mm
Deck Length 4T430CSS0x1	261"	6629 mm
Deck Length 4T430CSE0x1	297"	7544 mm
Deck Length 4T430CSX0x1	333"	8458 mm
Overall Width	150"	3810 mm
Deck Width	24"	610 mm
Lowered Height	10"	254 mm
Raised Height	70 1/4"	1784 mm
Minimum Wheelbase 4T430CSS0x1	230"	5842 mm
Minimum Wheelbase 4T430CSE0x1	230"	5842 mm
Minimum Wheelbase 4T430CSX0x1	230"	5842 mm
Maximum Wheelbase 4T430CSS0x1	231"	5867 mm
Maximum Wheelbase 4T430CSE0x1	267"	6782 mm
Maximum Wheelbase 4T430CSX0x1	303"	7696 mm
Lift Time	100 seconds	
Power Requirements	230 Volts AC - 60 Hz - 1 Ph - 20 Amp	
Shipping Weight	7,500 lbs	3402 kg

