

KANGO 750 S

7 kg class drilling and breaking hammer

Features

- Large, heavy weight striker delivers maximum 11.9 J impact energy
 - Powerful 1550 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
 - Fullwave electronics for precise power adjustment to application
 - Soft start for precise start of drilling/chiselling
 - AVS (Anti-Vibration-System) and soft grip on front and back handle
 - Additional handle can be fixed in 3 different positions
 - Soft hammer mode reduces blow energy for chiselling in sensitive materials
 - Roto-stop and multi-position chisel function
 - Service indicator light
-
- Variolock (12 positions) for selecting the most appropriate chisel angle
 - 6 m cable



BTCO



مركز البراغي والعدد
BOLTS & TOOLS CENTER LLC **BTCO**

| RANGE SPEC (1) | KANGO 750 S |
|--|------------------|
| Sound pressure level (dB(A)) | 96.4 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Sound power level (dB(A)) | 107.4 |
| Sound power level uncertainty (dB(A)) | 3 |
| Vibration chiselling uncertainty (m/s ²) | 1.5 |
| Vibration drilling into concrete [mls ²] | 9.5 |
| Vibration drilling into concrete uncertainty [mls ²] | 1.5 |
| No load speed (rpm) | 300 |
| Supplied in | Kitbox |
| Vibration drilling (m/s<special id ="27" />) | 9.5 |
| Vibration chiseling (m/s<special id ="27" />) | 9.1 |
| Max. drilling solid bit (mm) | 50 |
| Max. drilling core bit (mm) | 150 |
| Max. drilling tunnel bit (mm) | 80 |
| Article Number | 4933398600 |
| Full load speed (soft hammer) (rpm) | 240 |
| Weight (kg) | 8.2 [®] |
| Power input (W) | 1550 |
| Full load hammer action (bpm) | 2740 |
| Blow energy (EPTA)(J) | 11.9 |