

M12 HPT

M12™ sub compact Force Logic™ hydraulic press tool

Features

- The industry's smallest, lightest press tool: weighs only 1.8 kg for greater user comfort
 - REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
 - Patented one hand operation allows to work in restricted areas
 - Battery-tool communication: press operation doesn't start to prevent incomplete pressing in case of low charged battery. Pre-press battery check ensures enough charge to complete each press
 - Service intervals: advanced electronics count cycles and notify users when tool reaches calibration intervals
 - 4-step and precise battery status indicator
 - Press indicator: provides visual confirmation of a quality connection
 - Long-term reliability: goes an industry-leading 40,000 cycles between calibration inspections - the tool will not stop working after reaching 40,000 cycles
 - Outstanding pressing range up to 35 mm metal- and 40 mm composite pipes
- 
- BTCO**®
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
 - Fuel gauge displays remaining charge
 - REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
 - Flexible battery system: works with all Milwaukee® M12™ batteries

مركز البراغي والعدد
BTCO
BOLTS & TOOLS CENTER

RANGE SPEC (1)	M12 HPT-202C	M12 HPT-202C M-KIT	M12 HPT-202C V-KIT
Sound pressure level (dB(A))	75.5	75.5	75.5
Sound pressure level uncertainty (dB(A))	3	3	3
Sound power level (dB(A))	86.5	86.5	86.5
Sound power level uncertainty (dB(A))	3	3	3
Vibration level (m/s ²)	<2.5	<2.5	<2.5
Vibration uncertainty (m/s ²)	1.5	1.5	1.5
Voltage (V)	12	12	12
Battery pack capacity (Ah)	2.0	2.0	2.0
Battery type	Li-ion	Li-ion	Li-ion
Supplied in	Kitbox	Kitbox	Kitbox
Charger supplied	40 min	40 min	40 min
No. of batteries supplied	2	2	2
Article Number	4933443085	4933443095	4933443100
Weight with battery pack (kg)	1.8	1.8	1.8
Press cycles	40,000	40,000	40,000

RANGE SPEC (2)	M12 HPT-202C TH-KIT	M12 HPT-202C U-KIT
Sound pressure level (dB(A))	75.5	75.5
Sound pressure level uncertainty (dB(A))	3	3
Sound power level (dB(A))	86.5	86.5
Sound power level uncertainty (dB(A))	3	3
Vibration level (m/s ²)	<2.5	<2.5
Vibration uncertainty (m/s ²)	1.5	1.5
Voltage (V)	12	12
Battery pack capacity (Ah)	2.0	2.0
Battery type	Li-ion	Li-ion
Supplied in	Kitbox	Kitbox
Charger supplied	40 min	40 min
No. of batteries supplied	2	2
Article Number	4933443105	4933443110
Weight with battery pack (kg)	1.8	1.8
Press cycles	40,000	40,000