

## M18 BMS12

## M18™ compact metal shear

## **Features**

- Accurate cuts with maximum cutting depth of 1.2 mm in steel
- Unique 360° tool-free rotating head with 12 locking positions to access tight spaces and increasing user comfort
- REDLINK<sup>™</sup> overload protection electronics in tool and battery pack deliver best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- In-Line wrist design for increased control during cutting
- Variable speed trigger for extra control during cutting
- Belt clip for secure mobility
- REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
- Flexible battery system: works with all Milwaukee® M18™ batteries







RANGE SPEC (1)	M18 BMS12-0
Sound pressure level (dB(A))	78,2
Sound pressure level uncertainty (dB(A))	3,0
Sound power level measured (dB(A))	89,2
Sound power level measured uncertainty (dB(A))	3,0
No load speed (rpm)	0 - 2500
Vibration cutting of sheet metal [mls²]	4,75
Vibration cutting of sheet meta uncertaintyl [mls²]	1,5
Voltage (V)	18
Battery pack capacity (Ah)	_
Battery type	Li-ion
Supplied in	_
Charger supplied	
No. of batteries supplied	0
Article Number	4933447925
Weight with battery pack (kg)	2.3
Max. cutting capacity aluminium (mm)	2.0
Minimum cutting radius (mm)	180 (R)
Max. cutting capacity steel (mm)	1.2

