

# M18 CAG125X

## M18 FUEL™ 125 mm angle grinder

### Features

- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life
  - REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
  - REDLITHIUM-ION™ battery pack delivers up to 2.5x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
  - Premium gearing system - same system as used at high performance corded grinders
  - 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
  - 100% tool-free wheel change thanks to integrated FIXTEC system
  - Slimmest handle design available on market
  - Removable dust screen to prevent debris entrance, prolonging motor life
  - Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 
- Fuel gauge displays remaining charge
  - Flexible battery system: works with all Milwaukee® M18™ batteries



RANGE SPEC (1)	M18 CAG125X-0	M18 CAG125X-402C	M18 CAG125X-502C
Sound pressure level (dB(A))	83.2	83.2	83.2
Sound pressure level uncertainty (dB(A))	3	3	3
Sound power level (dB(A))	94.2	94.2	94.2
Sound power level uncertainty (dB(A))	3	3	3
Vibration grinding (m/s <sup>2</sup> )	3.4	3.4	3.4
Vibration grinding uncertainty (m/s <sup>2</sup> )	1.5	1.5	1.5
Vibration sanding (m/s <sup>2</sup> )	1.4	1.4	1.4
Vibration sanding uncertainty (m/s <sup>2</sup> )	1.5	1.5	1.5
No load speed (rpm)	8500	8500	8500
Voltage (V)	18	18	18
Battery pack capacity (Ah)	-	4.0	5.0
Battery type	Li-ion	Li-ion	Li-ion
accessory highlight	224921	224921	224921
Supplied in	-	Kitbox	Kitbox
Charger supplied	-	80 min	100 min
No. of batteries supplied	0	2	2
Spindle size	M 14	M 14	M 14
Article Number	4933443940	4933443950	4933448190
Weight with battery pack (kg)	-	2.5	2.5
Switch type	Slide switch	Slide switch	Slide switch
Max. cutting depth (mm)	33	33	33
Line lock out function	Yes	Yes	Yes
Disc diameter (mm)			125

مركز البراغي والعدد  
BOLTS & TOOLS CENTER **BTCO**

<b>RANGE SPEC (2)</b>	<b>M18 CAG125X-502X</b>
Sound pressure level (dB(A))	83.2
Sound pressure level uncertainty (dB(A))	3
Sound power level (dB(A))	94.2
Sound power level uncertainty (dB(A))	3
Vibration grinding (m/s <sup>2</sup> )	3.4
Vibration grinding uncertainty (m/s <sup>2</sup> )	1.5
Vibration sanding (m/s <sup>2</sup> )	1.4
Vibration sanding uncertainty (m/s <sup>2</sup> )	1.5
No load speed (rpm)	8500
Voltage (V)	18
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
accessory highlight	224921
Supplied in	HD Box
Charger supplied	59 min
No. of batteries supplied	2
Spindle size	M 14
Article Number	4933448866
Weight with battery pack (kg)	2.5
Switch type	Slide switch
Max. cutting depth (mm)	33
Line lock out function	Yes
Disc diameter (mm)	

مركز البراغي والعدد  
**BTCO**  
BOLTS & TOOLS CENTER