

MS 305 DB

12" (305 mm) dual bevel sliding mitre saw

Features

- Mitre angle digital readout - provides repeatable accuracy to 0.1°
- 1800 Watt direct drive motor with constant power technology
- Dual integral jobsite lights illuminate the cut line
- Integral dust channel captures 75% of all dust by capturing dust near the cut on both sides of the blade and directing it to the back of the saw
- Unique inline motor design - for excellent visibility from both sides to the work piece and better balanced transport
- Mitre capacity 55° to the left and 60° to the right - for maximum versatility. Mitre detents L & R at: 0°, 15°, 22.5°, 31.6°, 45°, 60°
- Dual-bevel design - to incline the saw head left & right 0° - 48° with bevel detents L & R at: 0°, 22.5°, 33.85°, 45°, 48°
- Fast and accurate bevel adjustment
- Supplied with workpiece clamp, saw blade (60 teeth), vacuum adaptor Ø 35 / 58 mm, wrench and 3 m cable



مركز البراغي والعدد
BTCO
BOLTS & TOOLS CENTER

RANGE SPEC (1)	MS 305 DB	MS 305 DB + AS 300 ELCP SET	MS 305 DB + MSUV 275 SET
Sound pressure level (dB(A))	95	95	95
Sound pressure level uncertainty (dB(A))	3	3	3
Sound power level (dB(A))	108	108	108
Sound power level uncertainty (dB(A))	3	3	3
Vibration cutting (m/s ²)	<2.5	-	-
Vibration cutting uncertainty (m/s ²)	1.5	1.5	1.5
No load speed (rpm)	3200	-	-
Product Relation_web	8755	8755	8755
Supplied in	-	-	-
Blade diameter (mm)	305	-	-
Article Number	4933411550	4933416448	4933416450
Weight (kg)	29.5	-	-
Power input (W)	1800	-	-
Max. cutting capacity 90<special id ="5" /> mitre/ 90<special id ="5" /> bevel (mm)	102 x 342	-	-
Max. cutting capacity 90<special id ="5" /> mitre/ 45<special id ="5" /> bevel (mm)	57 x 342	-	-
Max. cutting capacity 45<special id ="5" /> mitre/ 90<special id ="5" /> (mm)			-
Max. cutting capacity 45<special id ="5" /> 45<special id ="5" /> (mm)			-
Mitre capacity right (<special id ="5" />)	60	-	-
Mitre capacity left (<special id ="5" />)	55	-	-
Bevel capacity left (<special id ="5" />)	48	-	-
Bevel capacity right (<special id ="5" />)	48	-	-
Cable length (m)	3	-	-
Vibration cutting (m/s ²)	-	<2.5	<2.5

مركز البراغي والعدد
BOLTS & TOOLS CENTER 

RANGE SPEC (2)	MS 305 DB + MSL 3000 SET	
Sound pressure level (dB(A))	95	
Sound pressure level uncertainty (dB(A))	3	
Sound power level (dB(A))	108	
Sound power level uncertainty (dB(A))	3	
Vibration cutting (m/s ²)	-	
Vibration cutting uncertainty (m/s ²)	1.5	
No load speed (rpm)	-	
Product Relation_web	8755	
Supplied in	-	
Blade diameter (mm)	-	
Article Number	4933411623	
Weight (kg)	-	
Power input (W)	-	
Max. cutting capacity 90<special id = "5" /> mitre/ 90<special id = "5" /> bevel (mm)	-	
Max. cutting capacity 90<special id = "5" /> mitre/ 45<special id = "5" /> bevel (mm)	-	
Max. cutting capacity 45<special id = "5" /> mitre/ 90<special id = "5" /> (mm)	-	
Max. cutting capacity 45<special id = "5" /> 45<special id = "5" /> (mm)	-	
Mitre capacity right (<special id = "5" />)	-	
Mitre capacity left (<special id = "5" />)	-	
Bevel capacity left (<special id = "5" />)	-	
Bevel capacity right (<special id = "5" />)	-	
Cable length (m)	-	
Vibration cutting (m/s ²)	<2.5	

